

## KULATINY

Jakost	Rozměr [mm]	Rozměr [mm]	Jakost	Stav dodávky	Rozměr [mm]
1.2311	+QT	Ø 20 - Ø 70	1.0570 / S355J2G3	+AR +N	Ø 20 - Ø 650
1.2842 / NMV	+A	Ø 20,5 - Ø 230	1.6587 / 17HNM	+A +FP	Ø 50 - Ø 300
1.2063 / NC6	+A	Ø 10,2 - Ø 410	1.7131 / 16HG	+AR +A	Ø 20 - Ø 400
1.2201 / NC10	+A	Ø 15,5 - Ø 403	1.7141 / 20HG	+AR +A	Ø 20 - Ø 400
1.2080 / NC11	+A	Ø 20,5 - Ø 233	1.7147 / 18HGT	+AR	Ø 20 - Ø 180
1.2379 / NC11LV	+A	Ø 16 - Ø 323	1.0503 / C45	+AR +N	Ø 20 - Ø 650
1.2379 / NC11LV SUPREME*	+A	Ø 333 - Ø 423	1.0535/1.0601 C55/C60	+N	Ø 50 - Ø 250
1.2550 / NZ3	+A	Ø 20,5 - Ø 121,5	1.6580 / 30CrNiMo8	+A	Ø 125
1.4034 / 4H13	+A	Ø 16 - Ø 250	1.6582 / 34HNM	+A +QT	Ø 16 - Ø 400
1.3505 / LH15	+A	Ø 20,5 - Ø 200	1.7035 / 40H	+AR +A	Ø 20 - Ø 330
1.2343 / WCL	+A	Ø 15,5 - Ø 400	1.7225 / 40HM	+AR +A +QT	Ø 20 - Ø 805
1.2343 / WCL SUPREME*	+A	Ø 212 - Ø 302	1.8159 / 50HF	+AR +A	Ø 16 - Ø 160
1.2344 / WCLV	+A	Ø 25,5 - Ø 323			
1.3343 / SW7M SUPREME*	+A	Ø 10 - Ø 150			
1.2363	+A	Ø 19,25 - Ø 40,8			

## KULATINY TAŽENY STAV

Jakost	Stav dodávky	Rozměr [mm]
1.0570 / S355J2 tolerancja H9	+C +SH	Ø 12 - Ø 70
1.1191 / C45 tolerancja H9	+C +SH	Ø 12 - Ø 60
42CrMo4+QT tolerancja H9	+QT +SH	Ø 18 - Ø 65

## PLOCHÁ OCEL

Jakost	Stav dodávky	tloušťka [mm]	šířka [mm]
1.0570 / S355J2+N	+AR +N	20-90	205-605
1.0503 / C45 / 1.1730 / C45U	+A +N +S	20-90	205-605
1.2311 (280-320 HB)	+QT	20-90	200-605
1.2312 (280-320 HB)	+QT	20-90	205-605
1.2842 / NMV	+A	8-80	510-610
1.2063 / NC6	+A	8-120	70-610
1.2201 / NC10	+A	16-300	60-610
1.2080 / NC11	+A	8-80	170-800
1.2379 / NC11LV	+A	8-300	36-610
1.2550 / NZ3	+A	16-150	80-610
1.2083 / ~4H13	+A	8-120	400-610
1.2767	+A	300	800
1.2343 / WCL	+A	20-265	165-610
1.3343 / SW7M SUPREME*	+A	14-60	510

## PLECHY A BLOKY

Jakost	Stav dodávky	tloušťka [mm]	šířka [mm]	délka [mm]
1.0570 / S355J2	+AR +N	10 - 300	2000	3000-6000
S690QL	+QT	18	2000	2000-6000
HARDFIELD 400	+QT	5 - 60	2000	5100-6000
HARDFIELD 500	+QT	5 - 50	2000	5100-6000
1.7131 / 16 HG	+A +N	5 - 120	2000	5100-6000
1.7141 / 20 HG	+A +N	6 - 120	2000	5100-6000
1.0871 / 28MnB5	+AR	6 - 10	1500	3000
1.0503 / C45 / 1.1730 / C45U	+A +N +S +PI	1 - 300	1000-2000	2000-6000
1.0601 / C60	+AR	20 - 90	2000	4200-6000
1.7035 / 40H	+A +N +PI	2 - 120	1000-2000	2000-6000
1.7225 / 40HM	+A +N	8 - 300	2000	3500-6000
1.8159 / 50HF	+N +A +PI	0,5 - 12	1000-2000	2000-6000
1.2311 (280-320 HB)	+QT	18 - 350	1200-2000	3020-6000
1.2312 (280-320 HB)	+QT	15 - 505	990-2000	3000-6000
1.2316 (280-325 HB)	+QT	50, 300 - 350	900	4420-5210
1.2085 (29-32 HRC)	+QT	300	800	3200
1.2842 / NMV	+A	20 - 300	1000-2000	2500-6000
1.2714 / WNLV	+A	155 - 505	1000	2880-3700
1.2714 / WNLV (40-44 HRC)	+QT	155 - 505	1000	2880-3700
1.2343 SUPREME*	+A	185 - 400	1000	1000-5295
1.2344 SUPREME*	+A	300 - 400	1000	4535-4490
1.2738 (32-36 HRC)	+QT	205 - 500	1000-2000	1000-3630
1.2738 (38-42 HRC)	+QT	610	1000-2000	1000-3630
1.2738HH (38-42 HRC) SUPREME	+QT	150, 200, 610	1000	3000

## PÁSY

Jakost	Stav dodávky	tloušťka [mm]	délka [mm]
1.0601 / C60	+A	5	40
1.0603 / C67	+A	0,9-1,2	130-350
1.8159 / 50HF	+A	0,3-0,8	30-200